



8-Channel IP Gateway

model G1104-08



A complete, cloud-based intelligent video system with advanced analytics.

Reliable protection has never been this simple.

The KastleVideo 8-Channel IP Gateway (G1104-08) is a self-contained, Web-based intelligent video surveillance system with built-in advanced video analytics and recording for up to 8 channels of video. The IP Gateway includes always-on advanced video analytics that are 400% more accurate than motion detection, 24x7 recording, a digital matrix display and automatic Cloud backup, all combined into a compact low-power device. With an input capacity of up to 320 Megapixels/sec, the 8-Channel IP Gateway supports 4x8MP or 8x4MP cameras. It combines 24x7 on-premise recording combined with cloud backup in full 8MP resolution.

The 8-Channel IP Gateway works hand-in-hand with the KastleVideo Cloud VMS to provide all configuration, viewing and storage capabilities necessary for the user to realize the highest possible value from this solution. The KastleVideo Cloud VMS provides all ongoing management of up to 8 channels with off-site Cloud backup, multi-location federation and a powerful video search engine.

FEATURES



ADVANCED VIDEO ANALYTICS

Converts security cameras into intelligent video sensors by accurately detecting people, vehicles, loitering and zone-of-interest violations. Dramatically reduces false alarms by up to 85% vs. outdoor PIRs or cameras with built-in motion detection.



BUILT-IN DVR

24x7 video recording with remote playback, backup and search. NO additional hard-ware needed!



FULL CLOUD VMS

No software to download or install -- ever. Each channel has built-in tamper detection and 24/7 health monitoring.



MATRIX DISPLAY

A local matrix display is available on a connected HDMI monitor. View live video, play back recorded video, and control PTZ cameras through the intuitive user interface.

BENEFITS

KASTLEVIDEO Cloud VMS

All KastleVideo solutions feature 100% Web-based video management functionality with no servers or software installation required.

MULTI-SITE FEDERATION

View cameras from multiple sites or recorders through a single interface, without ever having to log into the recorder.

AUTOMATED SYSTEM HEALTH MONITORING

The system automatically issues proactive alerts in case of camera tampering, poor video quality or loss of communication.

VIDEO SEARCH ENGINE

Find relevant video in seconds, saves hours of time compared to traditional DVR's

BUILT-IN CYBER-SECURITY

Hacker-proof and secured against network attacks.



RECORDING

Format

24x7 recording of H.264
Main or High Profile

Supported Frame-Rate

5, 10, 15, 20, 25, or 30 fps

Recording Resolutions

720p default. Configurable up to 8 Megapixels

Hard Drive

Built in 6TB hard-drive records 8 cameras in high definition for up to 30 days.

VIDEO

Input Video

RTSP streams, 2 second GOV, ONVIF discovery (works with cameras that support ONVIF profiles that support S or T)

Resolutions

Supports up to 4x 8M or 8x 4M cameras. 320 Megapixels/second.

Video Playback

Local viewing, Web Playback, iPhone® and Android™ Apps

GENERAL

Dimensions

2" (h) x 12.3" (w) x 11.5" (d)

Connectors

Digital I/O 4 input 4 output
HDMI- monitor output or CVBS spot monitor
USB - mouse

Operating Conditions

0°C to 40°C (32°F to 104°F)
Humidity: 10% to 90%, no condensation

Power Source/Power Consumption

DC12V / 60W; 5.0A

Weight

6.1 lbs

Approvals

CE, FCC, RoHS

ALARM EVENTS (ANALYTICS)

Analytics Setup

Calibration-free, auto-adapting analytics
Classification and Tracking Engine
Moving person
Moving vehicles
Detects moving objects (eliminates environmental motion)
Zone violation
Loitering
Stopped vehicle
Unlimited polygonal detection zones

Video Alarm Clip

10-second video clip generated upon trigger of alarm, contains 2-4 seconds of pre-alarm video

Alarm Triggers

Presence of person, vehicle, or motion
Poor video
Loss of communication

Central Station Automation Integration

Bold Manitou, Micro Key MKMS, SIMS II/III, SureView Immix®, API available for integration to PSIMs

NETWORK

Wired

Dual 10/100/1000 Ethernet
LAN Port for camera with built-in DHCP server
WAN Port for Internet access

Security

HTTPS, IP Filter

Protocols

TCP/IP, UDP, HTTP, HTTPS, ICMP, DHCP, NTP

OUTPUT

Monitor

Supports external 1080p HDMI display

Live Matrix Display

2x2, 3x3 live display and PTZ control of ONVIF cameras

ACCESSORIES

Rack Mount Rail Kit

Rack mount rail kit part # 201183.

BACK PANEL

