



Viewing Station

model CVView

In a compact form factor, the perfect viewing complement to a KastleVideo solution.

Reliable protection has never been this simple.

The KastleVideo Viewing Station (CVVIEW) is a local viewer for on-site cameras. Live video is direct streamed from cameras and gateways with low latency. The CVVIEW is equally suited for guard desks, reception areas and command-center display walls and is compatible with standard HDMI displays. Matrix views from 4 to 36 live H.264/H.265 streams can be programmed for display.

The Viewing Station is a managed device and is remotely configured through the KastleVideo Video Management System. Local configuration of cameras is also possible by using a user login which enables tours and custom views. CVVIEW also receives and applies software updates automatically and requires no on-site maintenance. It continues to function and display video from local cameras even during loss of Internet connectivity.

SYSTEM

Fanless embedded computer with 4GB RAM capable of 1080p resolution

Dual HDMI Output

Port 1: HDMI 1.4, 1080p resolution

Port 2: HDMI 2.0, 4K resolution

Integrated 10/100/1000 Ethernet Network connection

ENVIRONMENT

Operating temperature

0° C to +50° C

Storage temperature

-10° C to +60° C

VIDEO

Inputs

IP video from up to 36 cameras. Supports KastleVideo cameras, Gateways and ExpressHD Recorders.

Configuration

Remote Management and view configuration 2x2, 3x3, 4x4, 5x5 or 6x6 matrix view

MECHANICAL

Dimensions

6.1" x 5" x 1.75" (154.9 mm x 127 mm x 44.45 mm)

VESA mount

Power

12V DC back panel power connector

12V, 36W power supply included